



SURFACE PREPARATION PRODUCTS

VCI-416

PRODUCT DESCRIPTION

VCI-416 is a heavy duty, water-based cleaner/degreaser offering unique corrosion protection. VCI-416 can provide protection for up to 12 months. VCI-416 is formulated to meet the requirements for cleaning and corrosion protection of parts and production equipment. VCI-416 penetrates to remove greases and oil deposits from machinery, engines, vehicles, construction equipment and cranes in either industrial or marine applications.

The compounds contained in VCI-416 function by altering hydrocarbons so that the deposits can be removed with water. VCI-416 can be metered into power washers, steam cleaners and other cleaning equipment. Along with good detergent properties, VCI-416 exhibits significant tolerance in the presence of calcium ions. As a result the performance of VCI-416 will not be compromised by water hardness.

While most cleaning compounds available on the market today are simple blends of surfactants and detergents which limit their effectiveness, VCI-416 offers improved cleaning plus multimetal corrosion protection action in one step, resulting in significant savings. VCI-416 has the unique ability to remove such deposits as heavy hydrocarbons, grease, drawing and buffing compounds, and machinery compounds. VCI-416 coats the metal surface with a tenacious film and mitigates the effect of oxidation upon the surface.

CHIEF ADVANTAGES

- Heavy duty chemical cleaner and degreaser with unique cleaning action for removing hydrocarbon deposits.
- Multimetal corrosion inhibitors leave a temporary protective coating, affording protection for a few months at 2.5 – 5% minimum concentration.*
- Provides exceptional resistance to pitting corrosion.
- Non-toxic, non-corrosive, does not contain nonylphenoethoxylates.
- Provides excellent cleaning action at low temperatures.
- Mild foaming.
- Effective at low concentrations.
- Exhibits good hard water tolerance.
- Formulation remains stable to freeze-thaw cycle.
- USDA approved.

*The estimated time of protection may vary due to conditions.

EFFECTIVE USES

- Machinery contaminated with oils.
- Sheet metal coated with temporary protective oils or waxes prior to painting, pickling or machining.
- Metal parts contaminated with stamping, drawing or buffing compounds.
- Use as an effective additive for rinse tanks to improve protection for dry storage applications (0.5 – 1.0% by weight).



CORTEC
CORPORATION

Environmentally Safe VCI/MCI® Technologies



APPLICATION

VCI-416 can be applied with any convenient equipment including sprayers, dipping tanks, steam cleaners and power washers.

Heavy-duty Cleaning

Use 1 part of VCI-416 to 5 – 10 parts water.

Normal Cleaning (i.e. parts washing)

Use 1 part of VCI-416 to 19 – 40 parts water.

Light Cleaning (i.e. rinsing)

Use 1 part VCI-416 to 40 – 150 parts water.

TYPICAL PROPERTIES

Appearance	Clear yellow liquid
Exposure Time	20 Seconds to 5 minutes
pH:	12 – 13
Weight per gallon	8.7 – 8.8 lb./gal. (1.04 – 1.06 kg/l)
Working temperature range	50° to 300°F (10° – 149°C)

PACKAGING

VCI-416 is available in 5 gallon (19 liter) and 55 gallon (208 liter) drums.

TOLL FREE CUSTOMER SERVICE
1-866-577-2326

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement product shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by: KPR ADCOR INC.

Phone (905) 628-3232, Fax (905) 628-2529

Toll Free (866) KPR-ADCOR , E-mail KPR@CORROSIONVCI.COM

Internet <http://www.corrosionvci.com>

printed on recycled paper 10% post consumer

Revised 3/98. Cortec®, Corwipe®, EcoSpray/EcoClean®, EcoWeave®, MCI®, Cor-Lube™, Cor-Mastic™, Cor-Pak™, Corrosorb™, EcoCoat™, EcoShield™, Electricor™, Migrating Corrosion Inhibitors™, Migratory Corrosion Inhibitors™, Primecoat™, Total Corrosion Control™, VCI Film Color of Blue™ and VHDRS™ are trademarks of Cortec Corporation.
© Cortec Corporation 1998. All rights reserved. Supersedes: 11/97



Certificate No. 43345